

Technical Datasheet

LL0220AA

1) Product Description:

LL0220AA is a linear low density polyethylene copolymer containing butane-1 (C4) as comonomer. It is suitable for blending with conventional LDPE for cast film applications. Film made from pure LL0220AA has the following advantages over LDPE: good balance of mechanical properties, good optical properties. This grade has food contact approval.

2) Applications:

- ✓ Light and medium duty films
- ✓ Stretch film

3) Typical data:

PROPERTIES	TEST METHOD	UNIT	TYPICAL VALUE*
Melt Flow Index (190°C 2.16 kg)	D 1238	g/10 min	2.4
Density	ASTM D 1505	gr/cm ³	0.921
Vicat Softening Point	ASTM D 1525	°C	100
Tensile stress at Yield	ASTM D 882	MPa	10/11
Tensile stress at Break	ASTM D 882	MPa	30/25
Dart Drop Impact	ASTM D 1709	GR	90
Elongation at Break	ASTM D 882	%	1000/1100
Haze	ASTM D 1003	%	1
Gloss (45°)	ASTM D 2457	%°	90

*All above mentioned data typical values and not to be construed as real specifications.

Address: No. 14, 1st floor, 23B, Tskneti Highway, Vake-Saburtalo Reg., Tbilisi, Georgia.

ZIP Code: 0162, Tel: +995 322434008/9, Email: info@mrchemicalge.com | www.mrchemicalge.com