

Technical Datasheet

POYAD AS100

1) Product Description:

- ✓ Product: Anti-Static Master-Batch
- ✓ Carrier: Poly Propylene (Homo Polymer)
- ✓ Active ingredients: Anti-Static Agent

2) Application:

- ✓ BOPP & CPP Film: 0.5 to 3% (depends on the Film Thickness & Requirement) in core layer
- ✓ PP Sheet: 0.5 to 2% (depends on the Sheet Thickness & Requirement)

Note 1: Thinner film/sheet needs more addition rate

Note 2: Humid climate needs less addition rate

Note 3: Anti-Static agent migrates to the film/sheet surface so potential problems in printing and sealing shall be considered.

3) Features & Advantages

- ✓ High absorption of moisture and eliminate electrostatic charge
- ✓ Lower the surface electrical resistivity
- ✓ Decrease the charge decay time

4) Typical data:

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE*
Melt Flow Rate (230 °C/2.16 Kg)	ASTM D1238	g/10min	6+2
Density	ASTM D 1505	g/cm ³	1.0
Moisture	ASTM D 644	%	Max 0.1
Bulk Density	PPT Method	g/cm ³	0.5

- ✓ Food contact approved ref. I.R.I Ministry of Health and Care.

Address: No. 14, 1st floor, 23B, Tskneti Highway, Vake-Saburtalo Reg., Tbilisi, Georgia.

ZIP Code: 0162, Tel: +995 322434008/9, Email: info@mrchemicalge.com | www.mrchemicalge.com