

Technical Datasheet

POYAD UV220

1) ProductDescription:

- ✓ Product: Light Stabilizer Master-Batch
- ✓ Carrier: Poly Ethylene
- ✓ Active ingredient: HALS

2) Application& Addition Rate:

- ✓ PE Greenhouse Film: 4 to 8%
- ✓ PE & PP Molded Parts: 1 to 5%

3) Advantages:

- ✓ Contain 20% of Synergic Mixture of HALS
- ✓ Enhance Light Stability
- ✓ Minimum Effect on Optical Properties
- ✓ Compatible Carrier Resin
- ✓ Odorless, Colorless

4) Typicaldata:

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE*
Melt Flow Rate (190°C/2.16 Kg)	ASTM D1238	g/10min	2.5±0.5
Density	ASTM D1505	g/cm ³	0.94
Moisture	ASTM D644	%	Max0.1

- ✓ Food contact approved ref. I.R.I Ministry of Health and Care.

Address: No. 14, 1st floor, 23B, Tskneti Highway, Vake-SaburtaloReg.,Tbilisi, Georgia.

ZIP Code: 0162, Tel: +995 322434008/9, Email: info@mrchemicalge.com | www.mrchemicalge.com